



Style 1617 - APPLIANCE WIRING MATERIAL

APPLIANCE WIRING MATERIAL

Subj. 758
Section 1
Page 1617

Issued: 1974-01-31
Revised: 2013-02-27

Style 1617 Single Conductor with Extruded Non-integral Covering

RATING 105 deg C, 600 Vac, Horizontal flame.

**INSULATED
CONDUCTOR** Labeled or complying with the manufacturer's AWM Procedure.

COVERING Extruded PVC, 5 mils minimum thickness at any point, 40 mils maximum thickness.

STANDARD Appliance Wiring Material UL 758.

MARKING General.

USE Internal Wiring.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"